



Founded in Spain in 1958

Metal Enclosures

HJXF Series

Standard: IEC/EN 60529

HJXF is a metal enclosure designed to be used with Himel MCB, RCBO, RCCB, and surge protection devices.

HJXF can be widely used in commercial and residential building.

Online Content



Product Views



Selection Code

Range name	Height	Width	Depth	Protection grade
HJXF	25	20	14	Q
HJXF: Metal Enclosure	25: 250 30: 200 40: 400 50: 500 60: 600 70: 700 80: 800 100: 1000	20: 200 25: 250 30: 300 40: 400 50: 500 60: 600 80: 800	14: 140 16: 160 18: 180 20: 200 25: 250 30: 300	Q: IP 54

Order Information

Type	Thickness	Dimension (mm)								Lock	Reference
		Overall			Installation		Mounting				
		H	W	D	H1	B1	H6	B6	Thick		
HJXF - 2520/14 IP54	1.2	250	200	140	310	150	172	122	2.0	1	HJXF252014Q
HJXF - 3025/14 IP54	1.2	300	250	140	360	200	222	172	2.0	1	HJXF302514Q
HJXF - 3025/18 IP54	1.2	300	250	180	360	265	222	172	2.0	1	HJXF302518Q
HJXF - 3030/14 IP54	1.2	300	300	140	360	265	222	222	2.0	1	HJXF303014Q
HJXF - 3030/18 IP54	1.2	300	300	180	360	265	222	222	2.0	1	HJXF303018Q
HJXF - 4030/14 IP54	1.2	400	300	140	460	365	322	222	2.0	1	HJXF403014Q
HJXF - 4030/20 IP54	1.2	400	300	200	460	365	322	222	2.0	1	HJXF403020Q
HJXF - 5040/14 IP54	1.2	500	400	140	560	465	422	322	2.0	2	HJXF504014Q
HJXF - 5040/20 IP54	1.2	500	400	200	560	465	422	322	2.0	2	HJXF504020Q
HJXF - 5040/25 IP54	1.2	500	400	250	560	465	422	322	2.0	2	HJXF504025Q
HJXF - 6040/14 IP54	1.5	600	400	140	660	565	522	322	2.0	2	HJXF604014Q
HJXF - 6040/20 IP54	1.5	600	400	200	660	565	522	322	2.0	2	HJXF604020Q
HJXF - 6040/25 IP54	1.5	600	400	250	660	565	522	322	2.0	2	HJXF604025Q
HJXF - 6050/14 IP54	1.5	600	500	140	660	565	522	422	2.0	2	HJXF605014Q
HJXF - 6050/20 IP54	1.5	600	500	200	660	565	522	422	2.0	2	HJXF605020Q
HJXF - 6050/25 IP54	1.5	600	500	250	660	565	522	422	2.0	2	HJXF605025Q
HJXF - 7050/16 IP54	1.5	700	500	160	760	665	622	422	2.0	2	HJXF705016Q
HJXF - 7050/20 IP54	1.5	700	500	200	760	665	622	422	2.0	2	HJXF705020Q
HJXF - 7050/25 IP54	1.5	700	500	250	760	665	622	422	2.0	2	HJXF705025Q
HJXF - 8060/20 IP54	1.5	800	600	200	860	765	722	522	2.0	2	HJXF806020Q
HJXF - 8060/25 IP54	1.5	800	600	250	860	765	722	522	2.0	2	HJXF806025Q
HJXF - 10080/20 IP54	1.5	1000	800	200	1060	965	922	722	2.0	2	HJXF1008020Q
HJXF - 10080/25 IP54	1.5	1000	800	250	1060	965	922	722	2.0	2	HJXF1008025Q
HJXF - 10080/30 IP54	1.5	1000	800	300	1060	965	922	722	2.0	2	HJXF1008030Q

Technical Parameters

Metal Enclosures	HJXF
Protection grade	IP43, IP54
Standard	IEC/EN60529
Sheet thickness	1.0 -1.5mm
Mounting plate thickness	1.0 -1.5mm
Hinge	Enhanced
Sealing rubber gasket	Black rubber gasket
Cable gland	Bottom only